

C&I-ISN SERIES

Different voltages for your choice/Reliable products for your diesel genset/4 Poles/Robust system/Customize according to your connection dimensions/Up to 100KW

● Reference Picture



● General Characteristics

MODEL	RATED POWER	MAX POWER	VOLTAGE	FREQUENCY	PHASE	POLES	EXCITING MODE	THD	CONNECTION DIMENSIONS	INSULATION CLASS	PROTECTION LEVEL
ISN02H	35.0	38.0	230V 120V/240V 230V/400V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
ISN04H	45.0	50.0	230V 120V/240V 230V/400V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
ISN06H	60.0	65.0	230V 120V/240V 230V/400V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
ISN07H	80.0	88.0	230V 120V/240V 230V/400V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
ISN08H	100.0	110.0	230V 120V/240V 230V/400V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23

● Dimensions Reference

