

C&I-IST SERIES

Different voltages for your choice/Reliable products for your diesel genset/4 Poles/Robust system/Customize according to your connection dimensions

Reference Picture



General Characteristics

MODEL	RATED POWER (KW)	MAX POWER (KW)	VOLTAGE (V)	FREQUENCY (Hz)	PHASE	POLES	EXCITING MODE	THD	CONNECTION DIMENSIONS	INSULATION CLASS	PROTECTION LEVEL
IST01H	16.0	18.0	115V/230V 120V/240V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
IST02H	20.0	22.0	115V/230V 120V/240V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
IST03H	24.0	26.0	115V/230V 120V/240V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
IST04H	30.0	30.0	115V/230V 120V/240V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23
IST05H	36.0	35.0	115V/230V 120V/240V	50Hz 60Hz	Single or Three	4	Brushed or Brushless	5%	SAE 5"-6"	CLASS H	IP23

Dimensions Reference

