

PORTABLE-PHN SERIES

2 type of end caps for choice, normal type and socket type/different voltages for your choice/Aluminum wire or copper wire/Customize your H class alternator for UL approval

Reference Picture



General Characteristics

MODEL	RATED POWER (KW)	MAX POWER (KW)	VOLTAGE (V)	FREQUENCY (Hz)	PHASE	POLES	EXCITING MODE	THD	SHAFT TAPER	INSULATION CLASS	PROTECTION LEVEL
PHN06H	4.0	4.5	230V 120V/240	50Hz 60Hz	Single or Three	2	Brushed or Brushless	<25% or < 5%	1:5 or 3:16	CLASS F/H	IP23
PHN09H	5.0	5.5	230V 120V/240	50Hz 60Hz	Single or Three	2	Brushed or Brushless	<25% or < 5%	1:5 or 3:16	CLASS F/H	IP23
PHN10H	6.5	7	230V 120V/240	50Hz 60Hz	Single or Three	2	Brushed or Brushless	<25% or < 5%	1:5 or 3:16	CLASS F/H	IP23
PHN13H	7.0	7.5	230V 120V/240	50Hz 60Hz	Single or Three	2	Brushed or Brushless	<25% or < 5%	1:5 or 3:16	CLASS F/H	IP23
PHN16H	8.0	8.5	230V 120V/240	50Hz 60Hz	Single or Three	2	Brushed or Brushless	<25% or < 5%	1:5 or 3:16	CLASS F/H	IP23

Dimensions Reference

